# **NEO S-Series Family**

## Automated tape libraries offer effortless backup and archive capabilities

In a world where the amount of corporate data generated doubles every 18 months and companies are legally bound to store the data long-term, IT managers are forced with the challenge of how to backup and archive data more efficiently and more affordably. Enter Overland Storage – where we recognize the need for your business to do more with less, and help address your small-to-medium sized business storage needs with the NEOs family of tape library solutions. Designed for IT offices with limited space, limited resources and limited budgets, the NEOs family delivers the ultimate in simple, affordable, reliable backup, archive and disaster recovery.

### Capabilities



- Remote Management
- Manage your NEO library from anywhere all you need is a web browser and a network connection
- The simple, intuitive interface makes administration easy
- Set alerts for backup and archive events



- Prevents unauthorized access to data
- Provides ability to securely transport cartridges offsite
- Facilitates data retention for regulatory compliance



- Removable Cartridge Magazines
- Secure, convenient media handling
- Effortless off-site transportation of cartridges for disaster recovery planning

backup systems. NEO S-Series tape libraries provide the capacities, features and efficiencies needed for archived data.

Reduces administrative costs



- Easy drag and drop functionality
- Familiar directory tree interface
- Eliminates the need for backup software



costs, improves use of valuable floor space, improves energy efficiency, provides a higher level of data security and improves performance of networks and disk-based

### Simple

Managing backups and archives can be a complex and costly activity. That's why NEOs is focused on providing a simple solution that reduces your administrative costs for backup and archive. Web-based remote management provides easy and convenient administration of the data archive process from anywhere in the world. Removable cartridge magazines enable easy access to data, reduce media handling costs and facilitate offline storage of your data for disaster recovery purposes. Standard barcode readers reduce media inventory times and simplify media management. Mail slots deliver easy, secure access to individual tape cartridges without interrupting library operations. NEO 200s and NEO 400s tape drives are easily added, removed or replaced, providing the flexibility to adapt to changing data storage requirements. Combine the NEOs ease-of-use features with its effortless configuration and installation and you will be backing up and archiving data in no time at all.

#### Affordable

NEOs doesn't just deliver an affordable purchase price - it also provides long-term cost of ownership advantages. NEOs ease-of-use features mean you spend less time managing your backup and archive, reducing your administrative costs. Because NEOs is an extremely reliable platform, service and maintenance costs are reduced and the costs associated with downtime and lost productivity are eliminated. Effortless upgradeability to next-generation technologies protect your investment long-term while allowing you to increase your storage capacities and transfer rates in order to keep up with the ever-increasing demand to store more and more data. NEOs not only protects your data but also protects your storage budget.

#### Compact

Available in rack-friendly 1u, 2u and 4u form factors, NEOs packs up to 75TB of data into a single unit of rack height. The ability to store so much data in such a small space minimizes the use of valuable rack space and reduces your overall cost of ownership.

### Versatile

Providing up to 300TB of data storage capacity, NEOs tape library solutions are not only designed to meet your data backup and archive needs today but allow you to grow in to, not out of, your storage. Available with SAS or Fibre Channel connectivity, NEOs easily integrates into your existing network infrastructure and provides easy-of-compatibility with 3rd party backup software applications. Utilizing industry-leading LTO tape drives, NEOs combines high-capacity storage with high-performance data transfer rates and increased backup and archive efficiency. Native partitioning capability in NEO 200s and NEO 400s libraries provides the ability to carve a single physical library into smaller logical libraries and securely use your NEOs library for a variety of different storage applications. NEOs libraries are the perfect solution for today's constantly-changing IT environment.

### **Specifications**

	NEO 100s	NEO 200s	NEO 400s
Configuration (total #)	cartridge slots magazines mailslots tape drives 9 1 1 1	cartridge slots magazines mailslots tape drives 24 2 1 1-2	cartridge slots magazines mailslots tape drives 48 4 3 1-4
Tape Drives Supported	LTO-6, LTO-5, LTO-4	LTO-6, LTO-5, LTO-4	LTO-6, LTO-5, LTO-4
Capacity (max)	uncompressed         compressed           LTO-6: 22.5TB         LTO-6: 56.3TB           LTO-5: 13.5TB         LTO-5: 27TB           LTO-4: 7.2TB         LTO-4: 14.4TB	uncompressed compressed LTO-6: 60TB LTO-6: 150TB LTO-5: 36TB LTO-5: 72TB LTO-4: 19.2TB LTO-4: 38.4TB	uncompressed         compressed           LTO-6: 120TB         LTO-6: 300TB           LTO-5: 72TB         LTO-5: 144TB           LTO-4: 38.4TB         LTO-4: 76.8TB
Transfer Rate (max # drives)	uncompressed compressed LTO-6: 576TB/hr LTO-6: 1.4TB/hr LTO-5: 504TB/hr LTO-5: 1TB/hr LTO-4: 432TB/hr LTO-4: 864GB/hr	uncompressed compressed LTO-6: 1.2TB/hr LTO-6: 2.9TB LTO-5: 1TB/hr LTO-5: 2TB LTO-4: 576TB/hr LTO-4: 1.2TB	uncompressed compressed LTO-6: 2.3TB/hr LTO-6: 5.8TB/hr LTO-5: 2TB/hr LTO-5: 4TB/hr LTO-4: 1.2TB/hr LTO-4: 2.4TB/hr
Reliability		MSBF (mean swaps between failures): 2,000,000 MTBF (mean time between failures): 100,000 hours	MSBF (mean swaps between failures): 2,000,000 MTBF (mean time between failures): 100,000 hours
Host Interface	LTO-6/LTO-5 LTO-4 6Gb SAS 3Gb SAS	LTO-6/LTO-5 LTO-4 6Gb SAS, 8Gb FC 24-slot: 3Gb SAS, 4GbFC	LTO-6/LTO-5 LTO-4 6Gb SAS, 8Gb FC 3Gb SAS, 4Gb
Connectors	Mini-SAS	Mini-SAS, LC optical FC	Mini-SAS, LC optical FC
User Interface	LCD front panel; web-based remote management	LCD front panel; web-based remote management	LCD front panel; web-based remote management
Physical Specifications	Dimensions: 1.73"(h) x 19.02"(w) x 33.46"(d) 1u	Dimensions: 3.44"(h) x 17.6"(w) x 29.13"(d) 2u Weight: 33 lbs (without rackmount)	Dimensions: 6.9"(h) x 17.6"(w) x 29.13"(d) 4u 47 lbs (without rackmount)
Power	100 - 240 VAC; 50 - 60 Hz; 110 watts (max)	100 - 240 VAC; 50 - 60 Hz; 168 watts (max)	100 - 240 VAC; 50 - 60 Hz; 312 watts (max)
Environmental Requirements	Humidity: 10-80% (operating, non-condensing) Temperature: 10 deg. C to 38 deg. C (operating)	Humidity: 10-80% (operating, non-condensing) Temperature: 10 deg. C to 45 deg. C (operating)	Humidity: 10-80% (operating, non-condensing) Temperature:10 deg. C to 45 deg. C (operating)
Standard Warranty	NEO S-Series products are covered by a one-year OverlandCare limited hardware warranty including Advanced Parts Replacement and 24x7 telephone support. NEOs libraries are eligible for enhanced maintenance options to augment the standard limited warranty. For full details of all of our service programs, please contact your preferred authorized reseller or contact Overland Storage at 1-858-571-5555.	NEO S-Series products are covered by a one-year OverlandCare limited hardware warranty including Advanced Parts Replacement and 24x7 telephone support. NEOs libraries are eligible for enhanced maintenance options to augment the standard limited warranty. For full details of all of our service programs, please contact your preferred authorized reseller or contact Overland Storage at 1-858-571-5555.	NEO S-Series products are covered by a one-year OverlandCare limited hardware warranty including Advanced Parts Replacement and 24x7 telephone support. NEOs libraries are eligible for enhanced maintenance options to augment the standard limited warranty. For full details of all of our service programs, please contact your preferred authorized reseller or contact Overland Storage at 1-858-571-5555.
Upgrade Options	1 year onsite, 3 years onsite	1 year onsite, 3 years onsite	1 year onsite, 3 years onsite
Agency Certifications	FCC Class A, EU 2004/108/EC, EN55022 Class A, China Class A EES, Taiwan Class A, VCCI, ICES-003, Korean Class A	FCC Class A, EU 2004/108/EC, EN55022 Class A, China Class A EES, Taiwan Class A, VCCI, ICES-003, Korean Class A	FCC Class A, EU 2004/108/EC, EN55022 Class A, China Class A EES, Taiwan Class A, VCCI, ICES-003, Korean Class A
Included in Std. Configuration	Library with (1) tape drive, US power cord, Quick Start Guide, rackmount hardware	Library with (1) tape drive, US power cord, Quick Start Guide, rackmount hardware	Library with (1) tape drive, US power cord, Quick Start Guide, rackmount hardware
Accessories	LTO-6/LTO-5/LTO-4 media, LTO cleaning cartridges, SAS connectivity kit, SAS host cables, LTO-6/LTO-5/LTO-4 barcode labels, 9-slot magazines	LTO-6/LTO-5/LTO-4 add-on tape drives, LTO-6/ LTO-5/LTO-4 media, LTO cleaning cartridges, SAS connectivity kit, SAS host cables, LTO-6/LTO-5/ LTO-4 barcode labels, 12-slot magazines	LTO-6/LTO-5/LTO-4 add-on tape drives, LTO-6/ LTO-5/LTO-4 media, LTO cleaning cartridges, SAS connectivity kit, SAS host cables, LTO-6/ LTO-5/LTO-4 barcode labels, 12-slot magazines

### **Sales Offices**

### North America

125 S. Market Street San Jose, CA 95113 USA

Tel: (858) 571-5555

overland storage.

#### Asia Pacific

16 New Industrial Road #04-04 Hudson TechnoCentre Singapore, 038988 Tel: +65 62811 525

#### France

18 Rue Jean Rostand Orsay 91400, France Tel: +33 1 81 91 73 40

#### Germany

Wilhelm Wagenfeld Straße 28 80807 München Germany Tel: +49 89 329 890 800

### **United Kingdom**

Ashville Way Wokingham, Berkshire RG41 2PL England Tel: +44 1 189 898 000

NEOSFam-DS1012-06

©2012 Overland Storage. All trademarks and registered trademarks are the property of their respective owners. The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. Overland Storage shall not be liable for technical or editorial errors or omissions contained herein.